

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ChiliTec GmbH

Supplier's address: Technik, Bäckerberg 12, 38165 Lehre, DE

Model identifier: 22568

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Wire		
Mains or non-mains:	MLS	Connected light source (CLS):	Nein
Colour-tuneable light source:	Nein	Envelope:	-
High luminance light source:	Nein		
Anti-glare shield:	Nein	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	3	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	100 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	2,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without	Height	Spectral power distribution in the	See image in last page
	Width		
	Depth		

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,400 0,300
Parameters for LED and OLED light sources:			
R9 colour rendering index value	-4	Survival factor	0,50
the lumen maintenance factor	0,70		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	8
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,9	Stroboscopic effect metric (SVM)	0,5

(a) : not applicable;

(b) : not applicable;

CIE Colorimetric Parameters

Chromaticity coordinates: $x=0.4244$ $y=0.3975$ $u(u')=0.2453$ $v=0.3446$ $v'=0.5169$
CCT: $T_c=3169K$ ($d_{uv}=-0.00078$) Color Ratio: $R=0.234$ $G=0.743$ $B=0.024$
Peak Wavelength: 605nm Half Bandwidth: 126.5nm
Dominant Wavelength: 583.4nm Color Purity: 0.467
Rendering Index: $R_a=80.6$
R1 =78 R2 =89 R3 =96 R4 =79 R5 =79 R6 =86 R7 =81 R8 =55
R9 =-4 R10=75 R11=78 R12=73 R13=81 R14=98 R15=71

